

# ICMP Control Messages

Type	Code	Status	Description
<b>0 – Echo Reply</b>	0		Echo reply (used to ping)
<b>1 and 2</b>		unassigned	Reserved
<b>3 – Destination Unreachable</b>	0		Destination network unreachable
	1		Destination host unreachable
	2		Destination protocol unreachable
	3		Destination port unreachable
	4		Fragmentation required, and DF flag set
	5		Source route failed
	6		Destination network unknown
	7		Destination host unknown
	8		Source host isolated
	9		Network administratively prohibited
	10		Host administratively prohibited
	11		Network unreachable for ToS
	12		Host unreachable for ToS
	13		Communication administratively prohibited
	14		Host Precedence Violation
15		Precedence cutoff in effect	
<b>4 – Source Quench</b>	0	deprecated	Source quench (congestion control)
<b>5 – Redirect Message</b>	0		Redirect Datagram for the Network
	1		Redirect Datagram for the Host
	2		Redirect Datagram for the ToS & network
	3		Redirect Datagram for the ToS & host
<b>6</b>		deprecated	Alternate Host Address
<b>7</b>		unassigned	Reserved
<b>8 – Echo Request</b>	0		Echo request (used to ping)
<b>9 – Router Advertisement</b>	0		Router Advertisement
<b>10 – Router Solicitation</b>	0		Router discovery/selection/solicitation
<b>11 – Time Exceeded</b>	0		TTL expired in transit
	1		Fragment reassembly time exceeded
<b>12 – Parameter Problem: Bad IP header</b>	0		Pointer indicates the error
	1		Missing a required option
	2		Bad length
<b>13 – Timestamp</b>	0		Timestamp
<b>14 – Timestamp Reply</b>	0		Timestamp reply
<b>15 – Information Request</b>	0	deprecated	Information Request
<b>16 – Information Reply</b>	0	deprecated	Information Reply
<b>17 – Address Mask Request</b>	0	deprecated	Address Mask Request
<b>18 – Address Mask Reply</b>	0	deprecated	Address Mask Reply
<b>19</b>		reserved	Reserved for security
<b>20 through 29</b>		reserved	Reserved for robustness experiment
<b>30 – Traceroute</b>	0	deprecated	Information Request
<b>39</b>		deprecated	SKIP Algorithm Discovery Protocol, Simple Key-Management for Internet Protocol
<b>40</b>			Photuris, Security failures
<b>41</b>		Experimental	ICMP for experimental mobility protocols such as Seamoby [RFC4065]
<b>42 – Extended Echo Request</b>	0		Request Extended Echo (XPing - see Extended Ping (Xping))
<b>43 – Extended Echo Reply</b>	0		No Error
	1		Malformed Query
	2		No Such Interface
	3		No Such Table Entry
	4		Multiple Interfaces Satisfy Query
<b>44 through 252</b>		unassigned	Reserved
<b>253</b>		Experimental	RFC3692-style Experiment 1
<b>254</b>		Experimental	RFC3692-style Experiment 2